

NEVILLE BUILT

SPRAYER/SPREADER TRAILERS

are designed to transport your sprayer/spreaders safely and quickly. We offer rigid or expandable trailers up to 12' wide in either fifth wheel or pintle hitch styles. A variety of tire and wheel combinations are available, as well as, spring or air-ride suspensions.

Custom Building A Trailer to Fit Your EXACT Needs is our Specialty!



53' Double Drop for Spreader or Sprayer





STANDARD 48' SPRAYER SPECIAL DROPDECK

- 11' upper deck 30" pin setting (10' and 12' optional)
- 37' of lower deck 40" deck height (35" deck height optional with 235/75R 17.5 tire option)
- REAR 21' of trailer equipped with 12' wide pullout extensions.
 Standard ride height for sprayer tires is 23". Optional 4" lower kit for 19" tire ride height and 8" lower kit for 15" sprayer tire ride height.
- 2 folding ramps for sprayer
- 11/2" oak flooring
- 5" high-tensile I-beam cross members
- Last 5' of main deck can be ordered as a beavertail to permit loading of tractors, trucks, loaders, etc.

TRAILER FEATURES

STANDARD

- 1. 25,000 # axles with 16½"x7" brakes, hub piloted 22.5 wheels, 25/1M ABS
- 2. New 255/70R22.5 virgin tires
- 3. Sealed wiring harness and rubber mounted lights
- Acid washed, hand sanded, epoxy primer & polyurethane paint

POPULAR OPTIONS

- Suspensions available: closed tandem (spring or air-ride) OR 10'1" spread (spring or air-ride)
- 2. Manual or electric dump valve for air-ride
- 3. Extensions can be dropped 4" to 19" or 8" to 15" sprayer tire carrying height
- 4. Special paint color
- 5. Machine finish or polished aluminum wheels
- 6. Bulkheads and folding sides

STANDARD 35' PINTLE HITCH SPRAYER TRAILER

- 35' long x 12' wide (available in rigid or expandable models)
- · Adjustable hitch height
- 21' of sprayer carrying area standard sprayer tire height 23", can be lowered 4" to 19" carrying height or lowered 8" to 15" carrying height
- Aluminum fenders over trailer tires

