

Henderson

MARK[™]E

SINGLE & TANDEM AXLE DUMP BODIES



Heavy-Duty Material Hauling Capabilities

The Dependable Ones[™]

All photos shown with optional equipment.



MARK E

SINGLE & TANDEM AXLE DUMP BODIES

The world's most customizable dump bodies. Build yours from a variety of options and accessories including side bracing, hoists, straight or sloped sides, materials and more.

Hoist Configuration Options


Start by selecting a hoist. The hoist controls a number of factors: appearance, function, placement, capacity and mounting height.

Underbody Hoist

A traditional hoist and sub-frame that stows underneath the body, providing a clean and clear head sheet.

Telescopic Hoist

Available with internal or external mounting and single (power up) or double (power up and down) acting function. Our telescopic hoist packages offer the lowest possible mounting height for a low center of gravity. The external telescopic hoist allows an optional full width cradle assembly for the hydraulic reservoir and valve enclosure. This provides a central location for your hydraulic components between the cab and head sheet.



UNDERBODY HOIST



TELESCOPIC HOIST
INTERNAL DOGHOUSE

TELESCOPIC HOIST
EXTERNAL DOGHOUSE



SLOPED SIDES

STEEL GRADES (Mix & Match)

Grade 50

AR400

201 Stainless

304 Stainless

Mix-n-match any of these materials for sides, tailgate, floor, etc.

CROSS-MEMBERLESS DESIGN

I-BEAM LONGITUDINALS

ASPHALT
REAR

Side Profile Options

Straight Sides (right)

This standard style helps trim both weight and cost. It also provides the ability to add sideboard inserts to increase capacity as needed. Steel sideboards are available or wood boards can be used.


Sloped Sides (above)

A permanent solution to maximize load hauling capacity. The degree of slope is determined by desired capacity. Additional accessories and options become available when selecting sloped sides.


Side/Brace Configuration Options



SMOOTH SIDES



V-CRIMP SIDES



WELD-ON HORIZONTAL BRACE SIDES

Smooth Sides

The basic style with the least weight and cost while offering excellent strength and resistance to wear. Additional benefits include easy clean out and ideal advertising space.

V-Crimp

Designed to increase side wall strength and help maintain its outward appearance. Side walls may allow up to four v-crumps.

Weld-on Horizontal Brace

The weld-on brace runs the length of the body. It maintains smooth inside walls for easy clean out and provides the ultimate side wall strength; ideal for maintaining the body's outward appearance.



**EXTRA-STRENGTH
CORNER POSTS**

**SIDEBOARD
POCKETS**

**STRAIGHT
SIDES**

INTEGRAL TARP
OPTIONAL

CAB SHIELD
OPTIONAL



COAL CHUTE
UP TO 3 - OPTIONAL

ASPHALT LIP
OPTIONAL

HIGH LIFT TAILGATE

**SIDEBOARD
POCKETS**



TARPS
OPTIONAL

**HIGH LIFT
TAILGATE**
OPTIONAL

Rear Tailgate Configuration Options



Straight Tailgate

Our most commonly selected style due to its array of flexible options. A great general purpose tailgate.

Also available in **Sloped** or **Asphalt Style** configurations.



MARK-E SINGLE AXLE DIMENSIONS & CAPACITY CHART

BODY LENGTH	BODY WIDTH INSIDE	SIDE HEIGHT	HEADSHEET HEIGHT	TAILGATE HEIGHT	CAPACITY SIDES/ENDS (cu. yd.)	RECOMMENDED CA	HOIST		
							TYPE	CLASS (NTEA)	CAPACITY (Tons)
TELESCOPIC HOIST									
10'	86"	24"	52"	32"	5.2/7.0	84"	M90-4.5-3	50	21.5
10'	86"	30"	52"	38"	6.5/8.3	84"	M90-4.5-3	50	21.5
10'	86"	36"	52"	44"	7.8/9.6	84"	M90-4.5-3	50	21.5
10'	86"	44"	52"	52"	9.6/11.3	84"	M90-4.5-3	50	21.5
11'	86"	24"	52"	32"	5.8/7.7	96"	M100-4.5-3	60	21.6
11'	86"	30"	52"	38"	7.2/9.1	96"	M100-4.5-3	60	21.6
11'	86"	36"	52"	44"	8.6/10.6	96"	M100-4.5-3	60	21.6
11'	86"	44"	52"	52"	10.6/12.5	96"	M100-4.5-3	60	21.6
12'	86"	24"	52"	32"	6.3/8.4	108"	M110-4.5-3	60	17.5
12'	86"	30"	52"	38"	7.9/10.0	108"	M110-4.5-3	60	17.5
12'	86"	36"	52"	44"	9.4/11.5	108"	M110-4.5-3	60	17.5
12'	86"	44"	52"	52"	11.5/13.6	108"	M110-4.5-3	60	17.5
UNDERBODY HOIST									
10'	86"	24"	52"	32"	5.3/7.1	84"	7-17	50	14.2
10'	86"	24"	52"	32"	5.3/7.1	84"	8-17	50	18.7
10'	86"	30"	52"	38"	6.6/8.4	84"	8-17	50	18.7
10'	86"	36"	52"	44"	8.0/9.7	84"	8-17	50	18.7
10'	86"	24"	52"	32"	5.3/7.1	84"	8-21	60	24.1
10'	86"	30"	52"	38"	6.6/8.4	84"	8-21	60	24.1
10'	86"	36"	52"	44"	8.0/9.7	84"	8-21	60	24.1
10'	86"	44"	52"	52"	9.7/11.5	84"	8-21	60	24.1
11'	86"	24"	52"	32"	5.8/7.8	96"	8-21	60	21.4
11'	86"	30"	52"	38"	7.3/9.2	96"	8-21	60	21.4
11'	86"	36"	52"	44"	8.8/10.7	96"	8-21	60	21.4
12'	86"	24"	52"	32"	6.4/8.5	108"	8-21	60	19.2
12'	86"	30"	52"	38"	8.0/10.1	108"	8-21	60	19.2

MARK-E TANDEM AXLE CAPACITY CHART

BODY LENGTH	BODY WIDTH INSIDE	SIDE HEIGHT	HEADSHEET HEIGHT	TAILGATE HEIGHT	CAPACITY SIDES/ENDS (cu. yd.)	RECOMMENDED CT	MAILHOT (single acting)	
							HOIST CLASS (NTEA)	CAPACITY (tons)
12'	86"	36"	60"	44"	9.6/11.7	96"	70	20.9
12'	86"	44"	60"	52"	11.7/13.8	96"	70	20.9
12'	86"	52"	60"	60"	13.8/15.9	96"	70	20.9
12'	86"	60"	60"	60"	15.9/15.9	96"	70	20.9
13'	86"	36"	60"	44"	10.4/12.7	108"	70	21.1
13'	86"	44"	60"	52"	12.7/15.0	108"	70	21.1
13'	86"	52"	60"	60"	15.0/17.3	108"	70	21.1
13'	86"	60"	60"	60"	17.3/17.3	108"	70	21.1
14'	86"	36"	60"	44"	11.1/13.6	120"	70	19.3
14'	86"	44"	60"	52"	13.6/16.1	120"	70	19.3
14'	86"	52"	60"	60"	16.1/18.6	120"	70	19.3
14'	86"	60"	60"	60"	18.6/18.6	120"	70	19.3
15'	86"	36"	60"	44"	11.9/14.6	132"	70	18.8
15'	86"	44"	60"	52"	14.6/17.3	132"	70	18.8
15'	86"	52"	60"	60"	17.3/19.9	132"	70	18.8
15'	86"	60"	60"	60"	19.9/19.9	132"	70	18.8
16'	86"	36"	60"	44"	12.7/15.6	144"	80	20.5
16'	86"	44"	60"	52"	15.6/18.4	144"	80	20.5
16'	86"	52"	60"	60"	18.4/21.2	144"	80	20.5
16'	86"	60"	60"	60"	21.2/21.2	144"	80	20.5
17'	86"	36"	60"	44"	13.5/16.5	156"	80	20.5
17'	86"	44"	60"	52"	16.5/19.6	156"	80	20.5
17'	86"	52"	60"	60"	19.6/22.6	156"	80	20.5
17'	86"	60"	60"	60"	22.6/22.6	156"	80	20.5
18'	86"	36"	60"	44"	14.3/17.5	168"	90	19.1
18'	86"	44"	60"	52"	17.5/20.7	168"	90	19.1
18'	86"	52"	60"	60"	20.7/23.9	168"	90	19.1
18'	86"	60"	60"	60"	23.9/23.9	168"	90	19.1
19'	86"	36"	60"	44"	15.1/18.1	180"	110	25.8
19'	86"	44"	60"	52"	18.5/21.5	180"	110	25.8
19'	86"	52"	60"	60"	25.2/28.2	180"	110	25.8
19'	86"	60"	60"	60"	25.2/25.2	180"	110	25.8
20'	86"	36"	60"	44"	15.9/18.9	192"	110	24.6
20'	86"	44"	60"	52"	19.4/22.4	192"	110	24.6
20'	86"	52"	60"	60"	23/26.0	192"	110	24.6
20'	86"	60"	60"	60"	26.5/26.5	192"	110	24.6

OPTIONS

CAB SHIELD

- Streamlined end plates.
- Gentle curves help prevent tarp damage.
- Designed to accommodate most vertical exhaust without modification.

SLOPING STEEL SIDEBOARD EXTENSIONS

Slopes front-to-rear. Top rail slopes outward the same as top rail, side braces and rub rail on body.

- Allows for improved weight distribution increasing payload.
- Streamlined, attractive appearance.
- Concept matches body design: durable and strong.

6 & 9-PANEL TAILGATE

- Available on 36", 44", 52" & 60" tailgates.

12-PANEL TAILGATE

- Available on 52" & 60" tailgates.

EXTRA HORIZONTAL TAILGATE BRACING

HIGH-LIFT TAILGATE

COAL CHUTE

BETWEEN-THE-FRAME HYDRAULIC TANK

SIDE LADDER, STEPS, WALKRAILS

VIBRATOR MOUNTS

TARPS

COAL CHUTES

ASPHALT LIP

304SS / 201 SS CONSTRUCTION

L.E.D. LIGHT KIT



Consult your local Henderson Distributor, as CA, CT and other installation related measurements may vary.

Additional accessories and options (not shown) are available.

*NTEA dump angle is 50°. Mark E body is 48.5°. Many single axle and some tandem axle Mark-E's have different mounting heights due to an additional sub-frame. All hoist ratings at 2000 psi.



1085 S. Third Street, Manchester, IA 52057
Toll Free: (800) 359-4970
www.HendersonProducts.com

Sourcewell
Formerly NJPA

CONTRACT: 080818-HPI



HP-021 6/18