

Liquid Tender Trailer





LIQUID TENDER TRAILERS

FEATURES

- 24" King pin
- Exterior mating surfaces are caulked prior to paint to prevent rust
- 2 aluminum steps with handrails
- Black plastic liquid tanks eliminate light from reaching the interior contents preventing algae and microbes growth
- 16.5" x 7" brake size, color coded
- Midship turn signals
- 255/70 R22.5 16 ply DOT tires and wheels
- Rubber mounted LED lights, DOT approved tape

MAIN BEAM SIZES

Web: 1/4" high grade 100,000 yield steel **Flange:** 3/8" x 5" high grade 100,000 yield steel **Cross members:** 4" x 3.2# 80,000 yield jr. I-beam on 16" centers

Side rails: 6" x 8.2# structural C channel

Rub rail: 2" x 3/8" flat steel

Beam rating: 50,000 lbs per 10 linear feet

DECKING

Material: 1 1/8" x 7" Apitong flooring **Transition Drop:** 19.5" between decks

SPECIFICATIONS

	42'	48'
Width	102"	102"
Capacity	55,000 lbs	55,000 lbs
Axles	Closed Tandem SAF Holland	Triple Axle SAF Holland
	Spring Ride (Optional Air Ride)	Air Ride ONLY
	2 x 22,500 (ABS on 1 axle)	3 x 23,000 (ABS on 1 axle)
Deck Length	15'6"	21'
GVWR	68,000 lb.	77,500 lb.



Optional storage bins



Black plastic liquid tanks eliminate light from reaching the interior contents preventing algae and microbes growth



Aluminum steps with handrails



Apitong Flooring

OPTIONS

- Air ride suspension for 42' trailer
- ABS installed on second axle
- Tank options: Den Hartog end and center drain tanks 2350, 2750, 3250 gallons
- Endroplast end or center drain on 2800 and 3200
- Storage bins: 3 on passenger side and 3 on drivers side
- Front and rear ladder options for 3250 gallon tank only
- Aluminum rims, hub piloted (each)
- Custom paint color (red, gray, white, blue)



Doing Our Best to Provide You the Best

4010 320th Street • Boyden, Iowa 51234 1.800.543.3626 www.demco-products.com