



# Neville Built Trailers

5581 SW 50<sup>th</sup> St. - Kingman, KS 67068  
800-301-3487 \* (620) 532-3487  
Fax: (620) 532-1125  
[www.nevillebuilt.com](http://www.nevillebuilt.com)  
email: [info@nevillebuilt.com](mailto:info@nevillebuilt.com)

## Dump Trailers



Neville Built full frame steel end dump trailers are available for your hauling needs. We offer a variety of sidewall height options in lengths of 24', 26' and 28'. Standard suspension is spring, however, air-ride or air-ride lift axles are available. We also offer a variety of tarp systems.



### Standard Specifications:

- 50,000 PSI minimum yield strength steel body (10 gauge sidewall and  $\frac{3}{16}$  floor)
- Muncie 5-stage hoist
- Grote sealed wiring system with rubber mounted LED lights
- 25,000# rated axles
- 9700 Hutch spring suspension (Ridewell air-ride option)
- Jost 2-speed heavy duty landing legs
- Tail gate chains



# Neville Built Trailers

5581 SW 50<sup>th</sup> St. - Kingman, KS 67068

800-301-3487 \* (620) 532-3487

Fax: (620) 532-1125

[www.nevillebuilt.com](http://www.nevillebuilt.com)

email: [info@nevillebuilt.com](mailto:info@nevillebuilt.com)

## Combine Trailers



Neville Built Combine Trailers are designed to transport your large combine safely and quickly from one job to another. We offer wide neck configurations in 28' and 34', as well as narrow necks up to 53'. We offer two or three axles on spring or air-ride suspension. We also offer pintle hitch combine trailers in two or three axle configurations. Our newest design is a patented complete hydraulic folding unit that will fold from 12'6" wide to 8'6" wide in just minutes with no manual lifting required!

### Standard Specifications

- 25,000# rated axles (16 ½ " or 12 ¼ " brakes)
- Fully sealed Grote wiring harness with rubber mounted LED lights
- PPG epoxy primer and polyurethane paint
- Hutch 9700 spring suspension with heavy duty springs

### Popular Options

- **FULLY HYDRAULIC FOLDING OUTRIGGERS**
- LED strobe lights
- Air-ride suspension
- Manual dump valve
- Aluminum wheels

**NEW  
PATENTED  
FEATURE!**



### Standard Transport Heights:

|                   | Main Frame Height | Combine Tire Transport Height |
|-------------------|-------------------|-------------------------------|
| 255/70R22.5 tires | 34"               | 20"                           |
| 245/70R17.5 tires | 31"               | 17"                           |